



# GAJAH TUNGGAL



## TRUCK & BUS

### GT MILER SUPER

DESIGNED FOR PAVED ROAD APPLICATION

- ▶ Maximum handling and braking performance on wet and dry surface.
- ▶ More comfortable ride and better steering response. Excellent grip to prevent slip.



| SIZE          | RIM | MAX LOAD (kg) |     |
|---------------|-----|---------------|-----|
|               |     | S             | D   |
| 640 x 13 8PR  | 5.0 | 750           | 710 |
| 650 x 14 8PR  | 4.5 | 840           | 795 |
| 700 x 14 8PR  | 5.0 | 785           | 750 |
| 650 x 15 8PR  | 4.5 | 875           | 835 |
| 650 x 16 10PR | 5.5 | 1,010         | 960 |

### GT MILER

DESIGNED FOR USE ON HIGHWAYS & NORMAL ROADS

- ▶ Provides maximum load carrying capacity and excellent riding stability at both maximum load condition and empty condition.
- ▶ Provides excellent grip on both dry and wet surface.
- ▶ Increases traction and long lasting.



| SIZE           | RIM | MAX LOAD (kg) |       |
|----------------|-----|---------------|-------|
|                |     | S             | D     |
| 825 x 20 14PR  | 6.5 | 2,030         | 1,930 |
| 900 x 20 14PR  | 7.0 | 2,415         | 2,300 |
| 1000 x 20 16PR | 7.5 | 3,000         | 2,650 |
| 1100 x 20 16PR | 8.0 | 3,350         | 2,900 |

### GT MILER SUPER 88N

DESIGNED FOR PAVED ROAD APPLICATION

- ▶ Good for heavy load and quick heat dissipation for longer and further operation.
- ▶ Excellent grip on dry and wet surface and better acceleration.
- ▶ Maximum water dispersion on wet surface. Optimum handling on heavy load condition.



| SIZE          | RIM | MAX LOAD (kg) |       |
|---------------|-----|---------------|-------|
|               |     | S             | D     |
| 500 x 12 8PR  | 3.5 | 485           | 465   |
| 600 x 14 8PR  | 4.5 | 750           | 710   |
| 700 x 15 10PR | 5.5 | 1,060         | 925   |
| 700 x 15 12PR | 5.5 | 1,180         | 1,120 |
| 750 x 15 12PR | 6.0 | 1,385         | 1,315 |
| 700 x 16 10PR | 5.5 | 1,100         | 965   |
| 700 x 16 12PR | 5.5 | 1,225         | 1,075 |
| 750 x 16 12PR | 6.0 | 1,440         | 1,370 |
| 750 x 16 14PR | 6.0 | 1,510         | 1,440 |
| 825 x 16 14PR | 6.5 | 1,710         | 1,630 |

### GT LUG

DESIGNED FOR EXTREME CONDITION

- ▶ Excellent traction on extreme mud surface and unpaved roads, quick heat dissipation with broad shoulder gap.
- ▶ Highly resistant to cut and chip, longer mileage and excellent grip on paved road.
- ▶ Provides heavy load bearing capacity



| SIZE           | RIM | MAX LOAD (kg) |       |
|----------------|-----|---------------|-------|
|                |     | S             | D     |
| 700 x 15 12PR  | 5.5 | 1,180         | 1,120 |
| 750 x 15 12PR  | 6.0 | 1,385         | 1,315 |
| 700 x 16 12PR  | 5.5 | 1,220         | 1,080 |
| 750 x 16 12PR  | 6.0 | 1,440         | 1,370 |
| 750 x 16 14PR  | 6.0 | 1,510         | 1,440 |
| 825 x 16 14PR  | 6.5 | 1,710         | 1,630 |
| 825 x 20 14PR  | 6.5 | 2,030         | 1,930 |
| 900 x 20 14PR  | 7.0 | 2,575         | 2,300 |
| 1000 x 20 16PR | 7.5 | 3,000         | 2,650 |
| 1100 x 20 16PR | 8.0 | 3,350         | 2,900 |



## INDUSTRIAL

### GT GRIP

DESIGNED FOR FORKLIFT APPLICATION

- ▶ Long lasting and provides exceptional grip on road surface, both inside and outside industrial area.
- ▶ Excellent stability, especially at industrial area. High mobility and efficiency.
- ▶ Increases grip ability for maximum load of the forklift.



| SIZE          | RIM | MAX LOAD (kg) |       |
|---------------|-----|---------------|-------|
|               |     | S             | D     |
| 600 x 9 10PR  | 4.0 | 1,905         | 1,410 |
| 650 x 10 10PR | 5.0 | 2,105         | 1,560 |
| 700 x 12 12PR | 5.0 | 2,775         | 2,055 |
| 825 x 15 14PR | 6.5 | 3,830         | 3,235 |

## TRUCK & BUS

### GT SUPER GRIP

SPECIALLY DESIGNED FOR LOGGING, MINING AND CONSTRUCTION WORKS

- ▶ Provides strong grip and maximum stability for heavy duty application.
- ▶ Highly resistant to tearing, cutting and snagging by rock.
- ▶ Good traction and quick mud self cleaning ability.



| SIZE           | RIM | MAX LOAD (kg) |       |
|----------------|-----|---------------|-------|
|                |     | S             | D     |
| 1000 x 20 16PR | 7.5 | 3,000         | 2,650 |
| 1100 x 20 16PR | 8.0 | 3,350         | 2,900 |
| 1200 x 24 18PR | 8.5 | 4,250         | 3,750 |
| 1200 x 24 20PR | 8.5 | 4,415         | 3,875 |
| 1200 x 20 18PR | 8.5 | 3,750         | 3,350 |

## OFF THE ROAD

### GT SUPER TRACTION

SPECIALLY DESIGNED FOR GOOD TRACTION AND FLOATING ON MUDDY GROUND

- ▶ Increases traction and grip on rocky or muddy terrain to maximize the performance of wheel loader.
- ▶ Excellent on every extreme condition and lasts longer to save on operational cost.
- ▶ Stronger tire wall and resistant to tear.



| SIZE               | RIM  | MAX LOAD (kg) | CODE |
|--------------------|------|---------------|------|
| 1300 x 24 12PR     | 8.0  | 2,575         | G2   |
| 1400 x 24 12PR     | 8.0  | 3,075         | G2   |
| 17.5 x 25 12PR     | 14.0 | 6,150         | L2   |
| 17.5 x 25 16PR     | 14.0 | 7,300         | L2   |
| 17.5 x 26 16PR T/L | 14.0 | 7,300         | L2   |
| 15.5 x 25 12PR     | 12.0 | 5,600         | L2   |

### GT ROCK GRIP

SPECIALLY DESIGNED TO HANDLE ALL KINDS OF TOUGH JOBS ANYWHERE

- ▶ Great maneuverability and grip on open pit / open mine or other extreme conditions.
- ▶ Long lasting and resistant to tears, cuts and snags. Heat resistant compound also helps the tire to cool down even faster.
- ▶ Helps the tire to cool down faster for higher TKPH (Ton Kilometer Per Hour) performance.



| SIZE            | RIM   | MAX LOAD (kg) |
|-----------------|-------|---------------|
| 16.00 x 25 28PR | 11.25 | 11,500        |
| 20.5 x 25 16PR  | 17.0  | 8,250         |
| 20.5 x 25 20PR  | 17.0  | 9,500         |
| 23.5 x 25 16PR  | 19.5  | 9,500         |
| 23.5 x 25 20PR  | 19.5  | 10,900        |
| 26.5 x 25 20PR  | 22.0  | 13,200        |
| 26.5 x 25 24PR  | 22.0  | 14,000        |
| 26.5 x 25 28PR  | 22.0  | 15,500        |

Manufactured by Giti Group



/gtradialphilippines



@gtradialph



gtradialph